

Composite Door

TECHNICAL DATA SHEET

Testing	
U-values	0.8 W/m2K
Accreditation	PAS24 & SBD
Specification	
Timber Core	44mm
Door Styles	40+
Frame	Chamfered / Sculptured
Woodgrain Skin	Woodgrain / Smooth / TrueGrain
Colour Options	250+ combinations
Locking	ABS & Multi-point as standard
Design options	
Optional Extras	Side Lights / Top Lights / Side Panels / Arched Frames
Open Options	Open In / Open Out
Threshold Options	Standard/ Low/ Integrated Cill
Glass Options	Decorative / Patterned
Hardware Colours	5+
Accessories	Letterplate Knockers Handle styles Bar Handles Pull Knobs Spyhole
Door restrictors (optional)	Graphite / Gold / Chrome / Black / Antique Black
Guarantee	10 years

**Results may vary based on specification. Further details available upon request*



*Image for indicative purposes only

Scope

UKO Group's composite door range has been designed to meet current and future building regulations, in addition to market-leading features such as our impressive 0.8 W/(m2K) U-value. Secure to PAS24 certification, the composite door exceeds Part L compliance with a new built requirement U-value is achieved when combined with standard features.

Materials

- 44mm solid timber core
- Chamfered or Sculptured frame
- Woodgrain, smooth or TrueGrain skin available
- ABS 3-Star rated cylinders as standard

Features

- Highly advanced secure locking mechanism
- All locks compliant to new building regulations, certified with the latest PAS24 standards.
- Market-leading composition, featuring: 44mm solid timber core and ABS locking system

Construction

The composite door range has been expertly manufactured by industry experts, hand selected by UKO Group for its impressive composition and longevity.

