

Flat Roof Light

TECHNICAL DATA SHEET

Sizes	
Minimum Size	L600mm x W600mm
Maximum Size	L3200mm x W2000mm
Stock Sizes	Made to measure sizes available 600 x 600 mm 750 x 750 mm 900 x 600 mm 900 x 900 mm 1000 x 1000 mm 1200 x 600 mm 1200 x 900 mm 1200 x 1200 mm 1500 x 1000 mm 2000 x 1500 mm
Average U-Values	
Typical U-Value	1.0 W/m ² K with standard glass, U-values can vary depending on glass specification
Glazing & Materials	
Glazing	Toughened glass as standard
Materials	Durable aluminium
Borders	Glass has 100mm black painted border
Testing	
Security	Rigorously tested to meet building regulations

**Results may vary based on specification. Further details available upon request*



*Image for indicative purposes only

Overview

UKO Group Flat Rooflights feature slim, minimalistic frames, toughened safety glass, and thermally broken profiles for efficiency.

Their contemporary design maximises natural light, enhances interior brightness, and offers durable, marine-grade coated finishes in multiple colours, with both stock and made-to-measure sizes available for versatile applications.

Finishes

- Available in 2 colours, Anthracite Grey (RAL 7016) or Black (RAL 9005) for both internal and external.
- Marine-grade powder coating for exceptional durability.
- Each rooflight is fitted with toughened glass as standard, prioritising the safety of those below.
- Slim, minimalistic framework.
- Glass has 100mm black painted border.

Construction

The flat roof light is constructed using the high-quality Sovu profile, providing market-leading performance alongside stunning aesthetics.

