

Roof Lantern

TECHNICAL DATA SHEET



*Image for indicative purposes only

Sizes	
Panes	Available in 4 or 6 panes
4 Pane Minimum Size	L800mm x W600mm
4 Pane Maximum Size	L3000mm x W2400mm
6 Pane Minimum Size	L1200mm x W700mm
6 Pane Maximum Size	L5000mm x W2000mm
Stock sizes	Made to measure sizes available 1500 x 1000 mm 2000 x 1000 mm 2000 x 1500 mm 2500 x 1000 mm 2500 x 1500 mm 2500 x 2000 mm 3000 x 1000 mm 3000 x 1500 mm 3000 x 2000 mm
Average U-Values	
Standard U-Value	1.2 W/m ² K with standard glass, U-values can vary depending on glass specification
Glazing & Materials	
Glazing	Toughened glass as standard
Materials	Durable aluminium
Testing	
Security	Rigorously tested to meet building regulations
Weather Durability	Advanced weatherproofing thanks to GUARD-Lock technology.

*Results may vary based on specification. Further details available upon request

Overview

UKO Group Roof Lanterns combine elegant design with high performance, flooding interiors with natural light while enhancing architectural appeal.

Expertly handcrafted in the UK, they offer durable construction, advanced glazing options, superior safety standards, and streamlined delivery, providing a premium, made-to-measure solution for modern residential and commercial spaces.

Finishes

- Available in 3 colours, Anthracite Grey (RAL 7016), White (RAL 9016) or Black (RAL 9005) for both internal and external, with dual colour options available.
- Toughened glass as standard.
- Marine-grade powder coating with dual colours available.
- Durable, slimline aluminium framing.
- Advanced weatherproofing thanks to GUARD-Lock technology.
- Available in 4 or 6 panes.

Construction

The roof lantern is constructed using a high-quality profile, providing market-leading performance alongside stunning aesthetics.

